



255 Fountain Street Akron, Ohio 44304-1991
330-535-2100 ♦ 800-321-2260 ♦ Fax 330-535-8947

SILICONE PRODUCTS -SPRAYS-

SILICONE SPRAYS

DESCRIPTION:

The following silicone sprays are mold release and lubricating agents formulated with high quality silicone polymers dispersed in a quick drying solvent carrier. These clear liquid sprays are available in 411 ml or 530 ml aerosol cans, 12 cans per case. The base silicones formulated in these release systems range in base silicone viscosity, content and modification (for paintable and urethane products). All of these products are CFC free and do not contain 1,1,1 trichloroethane.

TYPICAL PROPERTIES:

<i>Grade:</i>	<i>MR¹</i>	<i>7-Spray</i>	<i>S-903</i>	<i>S-711</i>	<i>PMR²</i>
ml/can	411	530	530	411	411
Silicone Content, %	8.0	11	5.0	11	6.5
Base Silicone Visco., cs	350	350	30,000	500,000	2,000
Flash Point, °C (open cup)	316	316	316	316	316
Specific Gravity	0.975	0.975	0.975	0.975	0.975

¹ mold release, ² paintable mold release

APPLICATIONS:

These versatile aerosol products are utilized as release agents in compression, transfer and injection processing of rubber, plastic and urethane articles. Other uses included lubricants to improve slip on coated surfaces, weather stripping and channels and during cutting operations. Specific formulating of these release systems provide key features such as: high water repellency and dielectric strength, colorless, non-staining residue, good thermal stability, fast drying properties and excellent lubricity. The MR (mold release) and 7-Spray grades are general release systems; 7-Spray contains a higher silicone content. S-903 contains a high viscosity base silicone and is used where a thicker coating is required. S-711 and PMR (paintable mold release) are specialty grades in which the base silicone has been modified with a resin or alkyl functionality. S-711 is formulated for cast and skin urethanes and epoxy products. PMR is a paintable mold release formulated for rubber and plastics products that require post finishing.

FLAMMABILITY:

These silicone sprays contain flammable petroleum solvents and propellants. Do not spray near open flames or ignition sources. See MSDS for more detailed information.

Included with its product literature and upon the request of its customers, Akrochem provides product specifications and evaluations, suggested formulations and recommendations and other technical assistance, both orally and in writing (collectively the "Technical Information"). Although Akrochem believes all Technical Information to be true and correct, it makes no warranty, either express or implied, as to the accuracy, completeness, or fitness of the Technical Information for any intended use, or the results which may be obtained by any person using the Technical Information. Akrochem will not be liable for any cost, loss or damage, in tort, contract or otherwise, arising from customer's use of Akrochem products or Technical Information. It is the customer's sole responsibility to test the products and any Technical Information provided to determine whether they are suitable for the customer's needs. Before working with any product, the customer must read

and become familiar with available information concerning its hazards, proper use, storage and handling, including all health, safety, and hygiene precautions recommended by the manufacturer. Nothing in the Technical Information is intended to be a recommendation to use any product, method, or process in violation of any intellectual property rights governing such product, method, or process. No license is implied or granted by Akrochem as to any such product, method, or process. AKROCHEM CORPORATION DISCLAIMS ANY AND ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR ANY PARTICULAR PURPOSE, RELATED TO ANY PRODUCTS OR TECHNICAL INFORMATION PROVIDED BY AKROCHEM.