



255 Fountain Street Akron, Ohio 44304-1991
 330-535-2100 ♦ 800-321-2260 ♦ Fax 330-535-8947

RUBBER CHEMICALS
-ACTIVATORS-

OLEIC ACID

DESCRIPTION:

Oleic Acid is a mixture of mono-unsaturated fatty acids primarily composed of cis-9-octadecenoic acid (oleic). Oleic acid (CAS #112-80-1) is derived from natural sources under tightly controlled conditions.

TYPICAL PROPERTIES:

Specific Gravity0.90
 Coloroyster White
 Form.....liquid

SHIPPING CONTAINER:

55 gal drum (approx. 410 lbs.), 5 gal plastic bucket (approx. 37 lbs.)

STORAGE:

Store in a cool, dry place with stock rotation of 30 days recommended. Protect from moisture.

GENERAL RECOMMENDATIONS:

Oleic Acid levels of 5.0 to 10.0 parts per 100 of rubber. Useful where color or clarity is not critical to the performance of the finished product.

MU080398
 T-ACAL80.DOC

Included with its product literature and upon the request of its customers, Akrochem provides product specifications and evaluations, suggested formulations and recommendations and other technical assistance, both orally and in writing (collectively the "Technical Information"). Although Akrochem believes all Technical Information to be true and correct, it makes no warranty, either express or implied, as to the accuracy, completeness, or fitness of the Technical Information for any intended use, or the results which may be obtained by any person using the Technical Information. Akrochem will not be liable for any cost, loss or damage, in tort, contract or otherwise, arising from customer's use of Akrochem products or Technical Information. It is the customer's sole responsibility to test the products and any Technical Information provided to determine whether they are suitable for the customer's needs. Before working with any product, the customer must read

and become familiar with available information concerning its hazards, proper use, storage and handling, including all health, safety, and hygiene precautions recommended by the manufacturer. Nothing in the Technical Information is intended to be a recommendation to use any product, method, or process in violation of any intellectual property rights governing such product, method, or process. No license is implied or granted by Akrochem as to any such product, method, or process. AKROCHEM CORPORATION DISCLAIMS ANY AND ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR ANY PARTICULAR PURPOSE, RELATED TO ANY PRODUCTS OR TECHNICAL INFORMATION PROVIDED BY AKROCHEM.