



255 Fountain Street Akron, Ohio 44304-1991
330-535-2100 ♦ 800-321-2260 ♦ Fax 330-535-8947

MINERAL FILLERS -SILICAS-

MANSIL[®] - 130G (granules)

DESCRIPTION:

Mansil-130G is a white precipitated silica in low-dusting granules. It is a reinforcing filler for use in synthetic and natural rubber compounding. The granulated form greatly reduces irritating dust for all applications where powdery material cannot be tolerated.

TYPICAL PROPERTIES:

	<u>Mansil- 130G</u>
Appearance	white granules
Moisture Loss- 105°C (%) (2 hrs in oven)	6 % max
pH(5% slurry)	6.0-7.0
Surface Area (m ² /g), BET	120-150
SiO ₂ , (%)	98.5 min
Oil Absorption, (DBP cc/100g)	220 min

APPLICATION:

Precipitated silica increases hardness, tensile strength, abrasion and tear resistance. For mechanical rubber goods, Mansil-130G can be used as the primary filler or in combination with carbon black. In tire applications, these silicas improve rolling resistance, flex fatigue and enhance traction. In adhesives compounding, silica provides an additional method of promoting improved adhesion, as well as providing reinforcement. Silicas are universally applied to provide increased abrasion resistance, green strength and translucence in the formulating of shoe sole compounds.

DOSAGE:

Lightly loaded compounds are prepared using 5 - 20 phr while highly loaded, oil extended compounds can use 75 - 100 phr. PEG-3350 is the most often used activator to improve cure rate and state of cure. Akrosorb 29471, which is dry liquid dispersion of 72% DEG, functions like PEG-3350 with the added advantage of further reduction of compound viscosity.

gpb 04/09
t-mansil-130G granulated