



255 Fountain Street Akron, Ohio 44304-1991
 330-535-2100 ♦ 800-321-2260 ♦ Fax 330-535-8947

RESINS & TACKIFIERS
-PHENOLICS-

P-03 RESIN
-TERPENE - PHENOLIC RESIN-

PRODUCT DESCRIPTION:

P-03 is a thermoplastic, oil soluble, high melting Terpene Phenolic Resin in flake form.

TYPICAL PROPERTIES:

Color.....	amber
Specific Gravity.....	1.10
Melting Point.....	150°C
Acid Number.....	65

STORAGE:

P-03 is a stable material with no tendency to change in physical properties when stored under normal conditions.

SHIPPING CONTAINERS:

Standard container is a 275 pound fiber drum or 50 pound bag.

GENERAL RECOMMENDATIONS:

P-03 is widely used to increase the open time of Neoprene solvent cements. The amounts used will vary from 10 to 150 parts per 100 parts of Neoprene. Although not as heat resistant as P-28, it provides more tack and is often used in combination with a heat reactive resin to give a balance of properties. It will show some reactivity with magnesium oxide but not to the amount experienced with a product such as P-28.

PRECAUTIONARY LABELLING:

In common with other supplies of plastics and chemicals, the precautionary label recommended by the Manufacturing Chemists Association for this material reads as follows:

CAUTION: MAY CAUSE IRRITATION

- Avoid prolonged contact with skin
- Avoid prolonged breathing of vapor or dust
- Use with adequate ventilation

cz021093
 T-P03.DOC

Included with its product literature and upon the request of its customers, Akrochem provides product specifications and evaluations, suggested formulations and recommendations and other technical assistance, both orally and in writing (collectively the "Technical Information"). Although Akrochem believes all Technical Information to be true and correct, it makes no warranty, either express or implied, as to the accuracy, completeness, or fitness of the Technical Information for any intended use, or the results which may be obtained by any person using the Technical Information. Akrochem will not be liable for any cost, loss or damage, in tort, contract or otherwise, arising from customer's use of Akrochem products or Technical Information. It is the customer's sole responsibility to test the products and any Technical Information provided to determine whether they are suitable for the customer's needs. Before working with any product, the customer must read

and become familiar with available information concerning its hazards, proper use, storage and handling, including all health, safety, and hygiene precautions recommended by the manufacturer. Nothing in the Technical Information is intended to be a recommendation to use any product, method, or process in violation of any intellectual property rights governing such product, method, or process. No license is implied or granted by Akrochem as to any such product, method, or process. AKROCHEM CORPORATION DISCLAIMS ANY AND ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR ANY PARTICULAR PURPOSE, RELATED TO ANY PRODUCTS OR TECHNICAL INFORMATION PROVIDED BY AKROCHEM.