



3770 Embassy Parkway Akron, Ohio 44333
 330-535-2100 ♦ 800-321-2260 ♦ Fax 330-535-8947

MINERAL FILLERS
-ADDITIONAL-

Sorbacid® 911

DESCRIPTION:

Sorbacid 911 is a synthetic, fine, white powder used as a lead replacement in halogenated polymers to scavenge acid by-products, which are detrimental to many polymeric processing and physical properties. Chemically, Sorbacid 911 is magnesium aluminum hydroxy carbonate. Sorbacid 911 has the added benefit of releasing water at 300°C (higher than ATH, thus safer processing) and therefore are used as flame-retardants and smoke suppressants. Sorbacid 911 product is environmentally safe, non-toxic, non-corrosive and non-volatile.

TYPICAL PROPERTIES:

Average particle size (d50, µm)	≤1
90% less than, µm.....	≤10
Density (g/cm ³).....	2.21
Moisture (105°C, 2hr).....	≤0.5%

APPLICATIONS:

Sorbacid 911 is primarily utilized as a lead oxide (e.g., litharge, red lead, BSWL) replacement to scavenge acidic byproducts in halogenated polymers such as: polychloroprene (CR), chlorosulfonated polyethylene (CSM), chlorinated polyethylene (CPE), epichlorohydrin (ECO), polyvinylchloride (PVC), fluoroelastomers (FKM) and halobutyls (BIIR, CIIR). In many formulations, these additives have successfully replaced lead oxides without disrupting any processing or physical properties of the compounds. In addition, these antacids provide superior water swell compared to magnesium oxides in all the elastomers stated above. In most formulations, lead oxides will show slightly better water swell behavior compared to Sorbacid 911 (it may help to also use epoxidized soybean oil as plasticizer to help with acid acceptance).

Sorbacid 911 can improve color of EPDM's by scavenging the acid chlorides left over from the polymerization process. Sorbacid 911 also has a special attribute of an internal decomposition and water release from 260°C to 300°C acting as flame-retardant and smoke suppressant. This product has been added to other flame retardant systems as inorganic stabilizer and smoke suppressant, especially with halogenated systems. Sorbacid 911 is also utilized in electrical applications for their anti-tracking properties. Compounds that could not be colored brightly due to lead content can now be made using Sorbacid 911.

gpb 11/18, t-Sorbacid 911

Included with its product literature and upon the request of its customers, Akrochem provides product specifications and evaluations, suggested formulations and recommendations and other technical assistance, both orally and in writing (collectively the "Technical Information"). Although Akrochem believes all Technical Information to be true and correct, it makes no warranty, either express or implied, as to the accuracy, completeness, or fitness of the Technical Information for any intended use, or the results which may be obtained by any person using the Technical Information. Akrochem will not be liable for any cost, loss or damage, in tort, contract or otherwise, arising from customer's use of Akrochem products or Technical Information. It is the customer's sole responsibility to test the products and any Technical Information provided to determine whether they are suitable for the customer's needs. Before working with any product, the

customer must read and become familiar with available information concerning its hazards, proper use, storage and handling, including all health, safety, and hygiene precautions recommended by the manufacturer. Nothing in the Technical Information is intended to be a recommendation to use any product, method, or process in violation of any intellectual property rights governing such product, method, or process. No license is implied or granted by Akrochem as to any such product, method, or process. AKROCHEM CORPORATION DISCLAIMS ANY AND ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR ANY PARTICULAR PURPOSE, RELATED TO ANY PRODUCTS OR TECHNICAL INFORMATION PROVIDED BY AKROCHEM.