

RUBBER RESIN

RIBETAK 7510



Description:

RIBETAK 7510 is an alkyl-phenol resin, thermoplastic type, in pastilles form.

Application:

RIBETAK 7510 is recommended as tackifier for synthetic and natural elastomers, featuring an excellent tack to green compounds made with synthetic or natural rubbers. This resin is specifically used in the manufacturing of tires, belts, hoses, etc.

Use recommendation:

RIBETAK 7510 is applied in a ratio of 2 to 10 parts by weight per 100 parts of rubber. When used with EPM or EPDM, this ratio should be among 5 to 10 parts by weight per 100 parts of rubber.

Characteristics:

Appearance	Amber Pastilles
Acid Number 739	50 - 70 mgKOH/g
Melting Point (R&B)	90 - 105 °C
Insoluble Acetone	Maximum 0.3 %
Ash Content	Maximum 0.1 %

Packaging:

RIBETAK 7510 is supplied in bags with 25 kg net weight.

Storage:

We recommend storing in a cool and dry place at room temperature.

Alkyl-phenol resins may occur variation in color, moisture absorption and agglomeration, during storage time.

In the recommended storage conditions, this product will have a 365 day shelf life, from the manufacturing date.

We also recommend observe the information contained in the respective MSDS (Material Safety Data Sheet).