

ZINC PRODUCTS
-ZINC OXIDES-

3770 EMBASSY PARKWAY AKRON, OHIO 44333 330-535-2100 ◆ 800-321-2260 ◆ FAX 330-535-8947

# ZINC OXIDE RGT-66T

### **DESCRIPTION:**

Zinc Oxide RGT-66T is a French Process Zinc Oxide made from zinc metal coated with propionic acid.

## **USES:**

Zinc Oxide RGT-66T is a general-purpose oxide serving as a cure activator in rubber compounds. Being a French process zinc, it can be used in white and colored rubber articles, where a zinc oxide of superior color is desirable. RGT-66T is useful in non-black articles to protect from UV weathering. The high heat transfer ability of ZnO means it is useful in dynamic applications where internal heat buildup is a problem. Ten phr or more of ZnO will transfer heat from the center of a product to the surface where it can be dissipated.

## **TYPICAL ANALYSIS:**

### Chemical:

ZnO (Dry Basis)	.99.8%
Pb	.0.003%
Cd	.0.001%
Fe	.nil
Cu	.nil
Propionic Acid	.0.10%

# Physical:

Surface Area	5.0 $m^2/g$
Mean Particle Size	0.22 microns
Specific Gravity	5.68 g/ml
Packing Density	30 lbs/ft <sup>3</sup>
Passing 325 mesh	99.98%

rh 2-5-24 T-RGT-66T (# 79042)